

MILA GARANT espags



- espags
- brakes
- accessory

www.mila.dk

 **MILA**
Quality & service | It's in our DNA

1. GENERAL INFORMATION

General Information

2. GARANT KOLVE- OG MINIHAGE-PASKVILLER

GARANT Tongue and Mini Hook Espags

3. BREMSER OG TILBEHØR

Brakes and Accessories

4. GARANT RULLEPASKVILLER M. SI-TAP

Garant Mushroom Espags

5. MONTERINGSVEJLEDNING

Mounting Instruction

6. VEDLIGEHOLDELSESVEJLEDNING

Maintenance Instruction

EGNE NOTATER

Notes

GENERELT

General info

1.

LÅSEKASSE

Grebshul 7 mm.

Skrueafstand 43 mm.

5 mm gevindhuller for grebsbefæstigelse.

Låsekassedybde:

Dornmål + 8 mm

Låsekasserne er forsynede med RBS*, hvilket vil sige, at kolverne/rullerne i lukket stilling kun kan betjenes via grebet.

* Reverse Blocking System

KOLVER

Kolvefremspring: 12 og 15 mm.

Kolvefremspring minihager: 14,6 mm

Lock Case

Handle hole 7mm.

Screw distance 43 mm.

5 mm thread holes for handle fixation.

Depth of lock case:

Backset measure + 8 mm


The lock cases are equipped with RBS* which means that tongues in locked position can be operated through the handle only.

* Reverse Blocking System

Tongues


Tongue projection 12 and 15 mm.

Mini hooks projection 14,6 mm




DORN / BACKSET

19, 25, 28, 33, 40 MM



KOLVEFREMSPRING
TONGUE PROJECTION
12 OG 15 MM



KOLVEFREMSPRING - MINI HAGE
TONGUE PROJECTION - MINI HOOK
14,6 MM

KOLVEPASKVILLER

Tongue Espags

2.

KOLVEPASKVIL STR. 1

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

Uden bremseoverføring

298–400 mm. Forsat grebshøjde 156 mm.

293–500 mm. Grebsplacering midte.

Med bremseoverføring

406–470 mm. Forsat grebshøjde 156 mm.

500–632 mm. Grebsplacering midte.

Tongue Espag Size 1

16 mm faceplate, silver finish. Lock case zinc alloy casting. 7 mm handle hole.

Serrated connector for brake both at top and bottom. Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Backset 19, 25, 28 and 33.

The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:

Without brake connector


298–400 mm. Offset handle height 156 mm.

293–500 mm. Central handle position.


With brake connector

406–470 mm. Offset handle height 156 mm.

500–632 mm. Central handle position.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038000	038120
25	038040	038160
28	038060	038180
33	038080	038200



KOLVEPASKVIL STR. 2

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

390–690 mm (uden bremseoverføring).

602–830 mm (med bremseoverføring).

Tongue Espag Size 2

*16 mm faceplate, silver finish. Lock case zinc alloy casting.
7 mm handle hole.*

*Serrated connector for brake both at top and bottom.
Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.*


Available in 19, 25, 28 and 33 mm backset.

The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.


Size Range:

390–690 mm (without brake connector).

602–830 mm (with brake connector).



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038002	038122
25	038042	038162
28	038062	038182
33	038082	038202



KOLVEPASKVIL STR. 3

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

590– 890 mm (uden bremseoverføring).

810–1020 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 3

16 mm faceplate, silver finish. Lock case zinc alloy casting.

7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:


590– 890 mm (without brake connector).

810–1020 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038004	038124
25	038044	038164
28	038064	038184
33	038084	038204



KOLVEPASKVIL STR. 4

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

800–1090 mm (uden bremseoverføring).

1010–1210 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 4

16 mm faceplate, silver finish. Lock case zinc alloy casting. 7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:


800–1090 mm (without brake connector).

1010–1210 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038006	038126
25	038046	038166
28	038066	038186
33	038086	038206



KOLVEPASKVIL STR. 5 / 5A

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Denne størrelse fås i 2 udgaver med henholdsvis 2 og 3 kolver. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

1000–1290 mm (uden bremseoverføring).

1210–1410 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 5 / 5A

16 mm faceplate, silver finish. Lock case zinc alloy casting. 7 mm handle hole.

Serrated connector for brake both at top and bottom.

This size is available with both 2 and 3 tongues. Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:

1000–1290 mm (without brake connector).

1210–1410 mm (with brake connector).


Sash lift optional.




STR. 5

STR. 5A

ARTIKELNR.				
Dornmål Backset	Kolve 12 mm 2 kolver/tongues	Kolve 12 mm 3 kolver/tongues	Kolve 15 mm 2 kolver/tongues	Kolve 15 mm 3 kolver/tongues
19	038008	038009	038128	038129
25	038048	038049	038168	038169
28	038068	038069	038188	038189
33	038088	038089	038208	038209



STR. 5



STR. 5A

KOLVEPASKVIL STR. 6

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

1200–1490 mm (uden bremseoverføring).

1410–1610 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 6

16 mm faceplate, silver finish. Lock case zinc alloy casting.

7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operate through the handle only.

Size Range:


1200–1490 mm (without brake connector).

1410–1610 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038010	038130
25	038050	038170
28	038070	038190
33	038090	038210



KOLVEPASKVIL STR. 7

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

1400–1690 mm (uden bremseoverføring).

1610–1810 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 7

16 mm faceplate, silver finish. Lock case zinc alloy casting.

7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operate through the handle only.

Size Range:


1400–1690 mm (without brake connector).

1610–1810 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038012	038132
25	038052	038172
28	038072	038192
33	038092	038212



KOLVEPASKVIL STR. 8

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28 eller 33.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

1600–1890 mm (uden bremseoverføring).

1810–2010 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 8

16 mm faceplate, silver finish. Lock case zinc alloy casting.

7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28 and 33 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operate through the handle only.

Size Range:


1600–1890 mm (without brake connector).

1810–2010 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038014	038134
25	038054	038174
28	038074	038194
33	038094	038214



KOLVEPASKVIL STR. 9

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28, 33 eller 40 mm.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

1900–2100 mm (uden bremseoverføring).

1920–2160 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 9

16 mm faceplate, silver finish. Lock case zinc alloy casting.

7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28, 33 and 40 mm backset.


The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:


1900–2100 mm (without brake connector).

1920–2160 mm (with brake connector).

Sash lift optional.



ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038016	038136
25	038056	038176
28	038076	038196
33	038096	038216
40	038116	038236



KOLVEPASKVIL STR. 10

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Tandstang foroven og forneden for kobling med bremse. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Dornmål 19, 25, 28, 33 eller 40 mm.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

2100–2300 mm (uden bremseoverføring).

2145–2360 mm (med bremseoverføring).

Rammeløfter kan monteres.

Tongue Espag Size 10

16 mm faceplate, silver finish. Lock case zinc alloy casting. 7 mm handle hole.

Serrated connector for brake both at top and bottom.

Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.

Available in 19, 25, 28, 33 and 40 mm backset.

The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.


Size Range:


2100–2300 mm (without brake connector).

2145–2360 mm (with brake connector).

Sash lift optional.

ARTIKELNR.		
Dornmål Backset	Kolve / Tongue 12 mm	Kolve / Tongue 15 mm
19	038018	038138
25	038058	038178
28	038078	038198
33	038098	038218
40	038118	038238





KOLVEPASKVIL STR. 2E OG 4E

Specialudgave af str. 2 og 4 med lang fortanding for yderligere afkortnings- og kombinationsmuligheder.

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul. Dornmål 25 og 28.

Tandstang foroven og forneden for kobling med forlængerstykker og bremser. Str. 2E er uden kolver, str. 4E har 1 kolve. Kolvefremspring 12 eller 15 mm. Grebsplacering kan forsættes fra midten ved hjælp af mellemstykker.

Paskvillen er forsynet med RBS, hvilket vil sige, at kolverne i lukket stilling kun kan betjenes via grebet.

Anvendelsesområde:

(med bremseoverføring/forlængerstk.)

2E: 635–1040 mm

4E: 1005–1650 mm

Tongue Espag Size 2E and 4E

Special execution of size 2 and 4 with long serrated rod for additional shortening and combination options.

16 mm faceplate, silver finish. Lock case zinc alloy casting. 7 mm handle hole. 25 and 28 mm backset.

Serrated rod at both top and bottom for coupling to extensions and brakes. Size 2E is without tongues, size 4E has one tongue. Tongue travel 12 or 15 mm. Handle position can be offset by means of connectors.


The espag is equipped with RBS which means that tongues in locked position can be operated through the handle only.

Size Range:

(with brake connector / extentions)

2E: 635–1040 mm



4E: 1005–1650 mm



STR. 2E

STR. 4E

ARTIKELNR.				
Dornmål Backset	Str. 2E kolve/tongue 12 mm	Str. 2E kolve/tongue 15 mm	Str. 4E kolve/tongue 12 mm	Str. 4E kolve/tongue 15 mm
25	038242	038244	038243	038245
28	038250	038252	038251	038253



BREMSE & TILBEHØR

Brakes & Accessories

3.

BREMSEOVERFØRING



16 mm fladstolpe, sølv finish.

For kobling med kolpepaskviller.

Brake Connector

16 mm flat faceplate, silver finish.

For coupling with tongue espags.





ARTIKELNR.		
Størrelse / Size	12 mm kolve	15 mm kolve
70 mm u. kolve	038272	038273
175 mm m. kolve	038275	038276

BREMSEOVERFØRING M. PILZTAP

Bremseoverføring med pilz-tap passende for hhv. MILA-GARANT og SIEGENIA AF fortanding. 16 mm fladstolpe, sølv finish.

Brake Connector with Mushroom Cam

Brake connector with mushroom cam suitable for MILA-GARANT and SIEGENIA AF toothing. 16 mm flat faceplate, silver finish.



ARTIKELNR.		
Type	9,5 mm tap / cam	15 mm tap / cam
AF fortanding / toothing	038297	038298

HJØRNE M. MINI-HAGE



16 mm fladstolpe, sølv finish CR3+

Solid mini-hage, modstår sidetryk på op til 6.000N (600kg) uden brud eller afbøjning.

Corner with Mini Hooks

16 mm flat faceplate, silver finish CR13+

Strong mini hook, tested for side pressure up till 6000N (600 kgs) without break or bending.



ARTIKELNR.	
Højre / RH	038398
Venstre / LH	038399

GREBSBETJENT FRIKTIONSREMSE

Sølv finish. Passer til standard euronot.

For kobling med kolve- og minihage-paskviller
via bremseoverføring.

Enkel montage med karmfæste




Handle Operated Brake

Silver finish. Fits standard Euro groove.


For coupling with tongue espags via brake connector .

Easy fitting by means of fixing bracket.




STR./SIZE 1

RFB/SRW: 280 - 500




STR./SIZE 2

RFB/SRW: 501 - 700



STR./SIZE 3

RFB/SRW: 701 - 900



STR./SIZE 4

RFB/SRW: 901 - 1100

ARTIKELNR.	
Størrelse / Size	Nr.
1	038280
2	038281
3	038282
4	038283
Forlængerkit for str. 4, Extension for size 4230mm	038284

GREBSBETJENT FRIKTIONSBREMSE M. BØRNESIKRING

Sølv finish. Passer til standard euronot.

For kobling med kolve- og minihage-paskviller
via bremseoverføring.

Enkel montage med karmfæste




Handle Operated Brake with Child Security Device

Silver finish. Fits standard Euro groove.


For coupling with tongue and mini hook espags via brake connector .

Easy fitting by means of fixing bracket.




STR./SIZE 1

RFB/SRW: 280 – 500




STR./SIZE 2

RFB/SRW: 501 – 700



STR./SIZE 3

RFB/SRW: 701 – 900



STR./SIZE 4

RFB/SRW: 901 – 1100






ARTIKELNR.	
Størrelse / Size	Nr.
1	038286
2	038287
3	038288
4	038289

KARMFÆSTER

Fixing Brackets

Karmfæste til hhv. 9 x 16, 5 x 16 og 7 x 12 mm not. Anvendes sammen med friktionsbremse.

Fixing bracket on for 9 x 16, 15 x 16 and 7 x 12 mm groove.
Is used with brake

Karmfæste 9 x 16 	
Karmfæste 5 x 16 	
Karmfæste 7 x 12 	
Karmfæste til iskruning Fixing Bracket Screw	

ARTIKELNR.	
9 x 16 mm not / groove	038290
5 x 16 mm not / groove	038291
7 x 12 mm not / groove	038292
Skrue / Screw	038375


FORLÆNGER- OG ENDESTYKKER

16 mm fladstolpe, sølv finish, for kobling med kolvepaskviller med både 12 og 15 mm kolvefremspring.


Extensions

16 mm flat faceplate, silver finish. For coupling with tongue espags with both 12 and 15 mm tongue projection.


ENDESTK. BUND
BOTTOM END PIECE




FORLÆNGERSTK. BUND
EXTENSION, BOTTOM




ENDESTK. TOP
TOP END PIECE



FORLÆNGERSTK. TOP
EXTENSION, TOP



FORLÆNGERSTK. UDEN KOLVE
EXTENTION, NO TONGUE



TL = TANDLÆNGDE / SERRATED


ARTIKELNR.		
Størrelse Size	Top / Bund Top / Bottom	Nr. No.
175	Top	038270
175	Bund	038271
271	Top	038380
271	Bund / Bottom	038384
480	Top	038382
480	Bund / Bottom	038386
271	Uden kolve No tongue	038383

ENDESTYKKER TIL MINIHAGE-PASKVILLER

16 mm fladstolpe, sølv finish, for kobling med minihage-paskviller med 14,6 mm fremspring.

End Pieces for Mini Hook Espags

16 mm flat faceplate, silver finish. For coupling with mini hook espags with 14,6 mm tongue projection.



FORLÆNGER, TOP
M. BREMSEOVERFØRING

FORLÆNGER, TOP
U. BREMSEOVERFØRING

FORLÆNGER, BUND
U. BREMSEOVERFØRING

TOP END PIECE
W. BRAKE CONNECTOR

TOP END PIECE
WITHOUT CONNECTOR

BOTTOM END PIECE
WITHOUT CONNECTOR

ARTIKELNR.		
Top / Bund Top / Bottom	Overføring Connector	Nr. No.
Top	med /with	038395
Top	uden / without	038396
Bund	uden / without	038397

PASKVILLER M. SI-TAP

Mushroom Espags

4.

RULLEPASKVILLER STR. 20 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.


Mushroom Espag Size 20

16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.



ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037600
25	9 mm	037640
28	9 mm	037660
33	9 mm	037540

RULLEPASKVILLER STR. 28 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.


Mushroom Espag Size 28

16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.



ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037602
25	9 mm	037642
28	9 mm	037662
33	9 mm	037542

RULLEPASKVILLER STR. 40 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.


Mushroom Espag Size 40

16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.



ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037604
25	9 mm	037644
28	9 mm	037664
33	9 mm	037544

RULLEPASKVILLER STR. 60 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.


Mushroom Espag Size 60

16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.



ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037606
25	9 mm	037646
28	9 mm	037666
33	9 mm	037546

RULLEPASKVILLER STR. 80 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.


Mushroom Espag Size 80

16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.



ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037608
25	9 mm	037648
28	9 mm	037668
33	9 mm	037548

RULLEPASKVILLER STR. 100 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.

Mushroom Espag Size 100


16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.

ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037610
25	9 mm	037650
28	9 mm	037670
33	9 mm	037550



RULLEPASKVILLER STR. 120 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.

Mushroom Espag Size 120


16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.

ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037612
25	9 mm	037652
28	9 mm	037672
33	9 mm	037552



RULLEPASKVILLER STR. 140 M. SIKKERHEDSTAP

16 mm fladstolpe, sølv finish. Låsekasse i støbt zink. 7 mm grebshul.

Dornmål: 19, 25, 28, 33, 40.

Paskvillen er forsynet med RBS, hvilket vil sige, at sikkerhedstappene i lukket stilling kun kan betjenes via grebet.

Mushroom Espag Size 140


16 mm flat faceplate. Silver finish.

Lock case in zinc diecast. 7 mm handle hole.

Backset: 19, 25, 28, 33, 40.

The lock cases are equipped with RBS, which means that the mushroom cams in closed position can be operated through the handle only.

ARTIKELNR.		
Dornmål Backset	Si-tap Mushroom	Nr. No.
19	9 mm	037614
25	9 mm	037654
28	9 mm	037674
33	9 mm	037554



MONITORING

Mounting

5.

MONTERINGSVEJLEDNING

Monteringsvejledning for elementer i træ og plast **uden overfals**, 4-5 mm falsluft, med beslagnot 9x16, 5x16 eller 7x12 mm i karm samt MILA GARANT bremseoverføring II.


Mål for placering af bremse og karmfæste er baseret på hængsel med en omdrejningsakse på

11 mm fra udvendig karmside og centerlinie midt i falsluft. Hvis omdrejningspunktet ændres som følge af anden hængselgeometri, vil åbningsvinklen ændre sig. Mål for placering skal da korrigeres tilsvarende.

Mounting Instruction


Mounting instruction for elements in timber and PVC **without rebate**, 4-5 mm air gap, and with a 9x16, 5x16 or 7x12 mm fitting groove in the frame and a MILA GARANT Brake Connector II.


Measurements of the position of brake and fixing bracket are based on hinges with an axis of rotation of 11 mm from surface of frame and a centre line between sash and frame. If the turning point differs from this, the opening angle will change. Consequently, measurements have to be corrected accordingly.



EKSEMPEL PÅ
TRÆRAMME MED
EURONOT.


EXAMPLE OF
TIMBER FRAME WITH
EURO GROOVE

MÅLSKEMA FOR BREMSE / KARMFÆSTE					
		BREMSE 1 Brake 1	BREMSE 2 Brake 2	BREMSE 3 Brake 3	BREMSE 4 Brake 4
		RFB/RBW 285 - 500 mm	RFB/RBW 451 - 700 mm	RFB/RBW 651 - 900 mm	RFB/RBW 851 - 1100 mm
	A (mm)	50	151	201	270
	B (mm)	25	120	214	325



KARMFÆSTE 038290
MONTERET I 9X16 MM
NOT.

FIXING BRACKET
038290 FITTED IN
9X16 MM GROOVE



KARMFÆSTE 038291
MONTERET I 5X16 MM
NOT.

FIXING BRACKET
038291 FITTED IN
5X16 MM GROOVE



KARMFÆSTE 038292
MONTERET I 7X12 MM
NOT.

FIXING BRACKET
038292 FITTED IN
7X12 MM GROOVE

MONTERING:

1. Rundstang afkortes i MILA GARANT klipper eller andet egnet klippeværktøj. For at sikre let samling mellem rundstang og bremsoverføring fjernes grater efter klipning. Man kan også med fordel lave en let tilspidsning af de yderste 2 mm.

Afkortning af rundstang (drejende del):
Længde C = RFB - B mål - 10 mm.
2. Overgang og bremse samles og placeres i noten hen over øverste hjørne. Beslagdelene fast-skrues, dog endnu ikke laskepladen.
3. Den afkortede paskvil placeres og samles med overgangen. Både trækstangen på paskvillen og tandskoen skal stå i nederst mulige stilling. Forbind tandstang i tandsko, og luk med laskepladen, som skydes hen over samlingen. Skrue isættes.

MOUNTING:


1. Shorten the round rod in the MILA GARANT cutter or any other suitable cutting device. To ensure easy connection between rod and converter, all burrs from the cropping must be removed. It is also a further advantage to make a leading edge size 2 mm.

Shortening of the round rod (rotating part):
Length C = RFB - B Dimension - 10 mm.
2. Converter and brake are connected and placed in the groove across the top corner. The parts are fixed by screws. However, do not yet fix the cover plate.
3. Insert the espag after this has been cut to length. Connect it to the converter after securing the correct position of both the shoe and pulling rod, both are to be in the maximum downward position. Slide the cover plate over the joint and fix it with a screw.

VEDLIGEHOLDELSE

Maintenance

6.



VEDLIGEHOELDELS- VEJLEDNING

Vedligeholdelsesvejledning for
kolvaskviller samt **bremse**.

Smøring:

De angivne punkter (det være sig
ruller eller kolver) smøres med syrefri
fedt minimum 1 gang pr. år eller efter
behov. Velsmurte kolver og slutblik
minimerer slitage og sikrer en lettere
gang af beslagene.

Glideskoen i bremsen må *ikke* smøres!
Den opadvendte kanal skal derimod
holdes ren for støv, sand og lignende.

Maintenance Instruction

*Maintenance instruction for cam and tongue
espags and **brakes**.*

Lubrication:

*Lubricate all cams/tongues and strikers as
indicated on the drawing at least once a year
with acid-free grease. Well lubricated tongues
and strikers minimise wear and tear, and ease
operation.*

*Do **not** lubricate the brake shoe!*

*However, the upward facing channel must be kept
free from dust, sand, etc.*

VIGTIGT:

Denne grebsbetjente bremse er IKKE et stop men alene beregnet til at fastholde
dør- eller vinduesrammen i den ønskede position under normale vindforhold.
Bremsen bør evt. suppleres med egentligt dørstop eller stormkrog.

IMPORTANT:

*This handle operated brake is NOT an actual stop, but a means to hold the door or
window frame in the desired position under normal wind conditions. We recommend
the brake is supplemented with an actual door stop or casement hook.*

MILA BESLAG A/S

H C Ørstedes Vej 18
DK-3000 Helsingør
Danmark
T. +45 49 13 99 00
E. info@mila.dk
www.mila.dk

MILA Baltics UAB

Kirtimu 59a
LT-02244 Vilnius
Lithuania
T. +370 5 2603200
E. info@mila.lt
www.mila.lt